

AVer EVC150

Full HD Endpoint



Package contents

- Main system unit (codec)
- The New eCam PTZ Camera (eCam PTZ II as follows)
- EVC microphone array
- IR remote control with batteries
- Power supply
- Cables
- Warranty card
- Quick guide

Communications

- H.323, SIP standards, SIP TLS
- 64Kbps~4Mbps
- RJ45 network LAN (10/100/1000)
- Manual bandwidth settings

Camera

eCam PTZ II:

- Pan/tilt/zoom camera
- 2-mega pixel CMOS sensor
- 18X total zoom (12X optical + 1.5X digital zoom)
- ±130° pan; +90°/-25° tilt
- 72° FOV (H); 43° FOV (V); 82° FOV (diagonal)

People video resolutions

- HD1080p (1920 x 1080)
- HD720p (1280 x 720)
- 480p (848 x 480)
- 4CIF (704 x 576)
- 4SIF (704 x 480)
- 360p (640 x 360)
- W288p (512 x 288)
- CIF (352 x 288)
- SIF (352 x 240)
- All resolutions at 30fps

Content video resolutions

Supported resolutions:

- WSXGA (1440 x 900)
- HD (1360 x 768)
- SXGA (1280 x 1024)
- QVGA (1280 x 960)
- WXGA (1280 x 800)
- XGA (1024 x 768)
- SVGA (800 x 600)
- VGA (640 x 480)

Output resolutions:

- HD720p (1280 x 720) up to 30fps

Video standards

- H.264, H.264 HP, H.264 SVC, H.263+, H.263, H.261
- H.239 dual video streams
- BFCP content sharing

Video inputs

- eCam PTZ II
- VGA

Video outputs

- HDMI
- VGA

Audio standards

- G.711, G.722, G.728, G.722.1, G.722.1C

Audio features

- Automatic gain control (AGC)
- Advanced noise reduction
- Acoustic echo cancellation (AEC)

Audio inputs

- EVC microphone daisy chain up to 4
- Line-in (3.5 mm)

Audio outputs

- HDMI
- Line-out (3.5 mm)

Other supported standards

- H.224, H.225, H.245, H.281, H.323 Annex Q, H.460
- SRTP

User interface

- Multiple layout styles
- User-friendly OSD (22 supported languages: English, Traditional Chinese, Simplified Chinese, Czech, Danish, Dutch, Finnish, French, German, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese-Brazil, Romanian, Russian, Spanish, Swedish, Thai, Turkish)
- Display/edit site name

Network

- 10/100/1000Mbps
- NAT/firewall traversal (H.460)
- High Efficiency Lost Packet Recovery (HELPeR™)
- API support via Telnet
- Wake-on-LAN (WOL) support
- IPv4 and IPv6 support
- Quality of Service (QoS)
- Network test

Security

- AES (Advanced Encryption Standard) function (128-bit)
- Password protection for system settings
- Password protection for remote system management

Web management tool

- Remote management
- Live monitoring
- Firmware update
- Phonebook download/upload/edit
- Restore system settings
- Export call history

Value-added features

- Meeting recording
 - In meeting and offline recording
 - Save directly to USB flash drive
 - Supports screen re-layout during playback
 - Playback and file conversion via VCPlayer software (.mov and .mp4 format)
- Dual monitor
- Speed dialing via hot keys (10 sets)
- Camera presets (100 positions)
- Network Time Protocol (NTP)
- Firmware update via USB flash driver
- Screensaver and auto power off mode
- ScreenShare
- VCLink
- LDAP directory
- Supports SIP voice calls

- SnapShot

Power supply

- AC 100V~240V, 50/60Hz
- Consumption: EIAJ 12V, 4A

Environmental Data

- Operation temperature: 0~40°C
- Operation humidity: 20%~80%
- Storage temperature: -20~60°C
- Storage humidity: 20%~80%

Physical characteristics

- Package dimensions: 376 x 300 x 243mm
- Package weight: 6.49kg (14.31lbs)
- Main system (codec): 260 x 158.7 x 33mm
- eCam PTZ II: 180 x 144 x 184mm
- EVC microphone array: 131.9 x 118.6 x 25.5mm

Optional accessories

- Additional microphone
- Camera mount
- Replacement eCam PTZ camera

Warranty

- 3-year standard warranty*

* Please register online to receive free 2 year warranty extension. For detailed warranty information, please contact an AVer representative.

eCam PTZ II



Hardware specifications

Front panel



Back panel

