

[Tentative]

EK-120U

4,400 Lumens / WUXGA / 3LCD
"Entry" Series Projector
Crestron RoomView™ & AMX Device Discovery Technology

EK-120U

4,400 center lumens bright with 80% uniformity and a 15,000:1 contrast ratio.

Native WUXGA resolution. Compatible with inputs up-to UXGA and WUXGA.

Supports analog and digital video input in all color standards up-to 1080p.

HDMI with MHL (Mobile High-Definition Link) displays HD Video from Smartphones & Tablets.

Convenient mid-range (1.66:1) manual zoom and focus lens.

Horizontal, Vertical & Corner Keystone Correction.

Accepts composite, component, and S-Video in all major standards.


Displays both 4:3 and 16:9 aspect ratios. Supports most HDTV resolutions.

Built-in 10 Watt sound system. Closed Caption decoding (NTSC). Wired network control.

Side-accessed air filter for ease of maintenance. Auto input selection. Built-in Test Patterns.

Security bar. Kensington® MicroSaver® security slot. PIN lock.

3 year projector warranty.



Included Accessories

Quick Start Guide, 5.0 ft (1.5 m) VGA Cable, 6.0 ft (1.8 m) Detachable Power Cord, Remote Control (with 2x AAA Batteries)

Optional Accessories:

Replacement Lamp, Replacement Filter, Component Video Cable (3RCA to Dsub15), Ceiling Mount, Ceiling Post and Plate

Specifications: Model EK-120U

Brightness	4,400 Center Lumens	Image Signal Inputs
Contrast Ratio	15,000:1	Computer 1 (Compo
Illumination Uniformity	80%	Digital Video (w/ HD
Resolution and Aspect Ratio	WUXGA (1920x1200), 16:10	USB Type A - Memo
Color Reproduction	10-bit (16.7 million colors)	USB Type B - USB D
Projection Lamp	225 Watts UHP	Composite Video
Estimated Lamp Life (Eco / Normal)	20,000 / 10,000 hours	Audio Signal Inputs
Total Pixels	6,912,000 (1920x1200) x 3	Computer Audio
Imaging System	0.64 in (16 mm) inorganic LCD Panels x 3	Video Audio
Scanning Frequency	Auto: H Sync. 15-91 KHz, V Sync. 24-85 Hz	Outputs
Pixel Clock	up-to 160 MHz	Computer Monitor
Lens	Attached - Manual Zoom and Focus	Audio Output
Lens Specs	<i>f</i> : 1.7-2.11; FL: 0.689-1.142 in (17.50-29.01 mm)	Amplifier
Lens Ratios	Zoom Max:Min: 1.66:1; Throw:Width 1.26-2.09:1	Speaker
Image Diagonal	30-300 in (76.2-762 cm)	Fan Noise (Eco / Norr
Image Width	2.6-27.5 ft (0.8-8.4 m)	Cabinet Size (HxWxD
Throw Distance	2.66-45.50 ft (0.812-13.869 m)	Weight
Projector Elevation Adjustment (legs)	up-to 10°	Packaged Cabinet Siz
Maximum Pitch	Up-to 10° Up or Down	Packaged Weight
Anti Keystone	Fixed Image Offset, Ratio (Top/Bottom) 8.71:1	Operating Temperatu
Vert/Horiz. Keystone Correction	Digital:V:+/- 30° - H: +/- 15°, Corner Keystone	Electrical Safety Com
Image Orientation	Normal, Reversed, Inverted	Electromagnetic Com
Local Control / Power Management	Full Function / Auto Shutdown	Power Requirements
Remote Control	Wireless x 1	Power Consumption
RS-232 Control	Dsub9 x 1	Heat
LAN Port	RJ45 x 1	Security Facilities
Computer Input in Pixels	up-to 1600x1200 (4:3), 1920x1200 (16:10)	UPC
Analog 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC	User Maintenance
Analog Wide Inputs	WUXGA, WSXGA+, WXGA	Limited Warranty: to
Digital 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC	Projector
Digital Wide Inputs	WUXGA, WSXGA+, WXGA	Lamp
Video Formats	NTSC / PAL / SECAM	
Video Input Analog	480i/p, 575i/p	
Video Input Digital	480p, 575p, 720p, 1080i/p	
Image Signal Resizing	Smart Scaling Technology	

Dsub15 x 1		
HDMI x 2		
USB Type A x 1		
USB Type B x 1		
RCA x 1		
MiniStereo x 1		
RCA x 2 (L/R)		
Dsub15 x 1		
Variable, Stereo: MiniStereo x 1		
Mono: 10 Watt		
1.4 in (3.7 cm) x 1 (Mono)		
30.0 dB / 37.0 dB		
3.9 x 13.6 x 10.3 in (9.9 x 34.5 x 26.1 cm)		
7.0 lb (3.2 kg)		
7.7 x 17.4 x 15.2 in (19.5 x 44.2 x 38.6 cm)		
10.4 lb (4.7 kg)		
41-95°F (5-35°C)		
IEC / UL / cUL		
FCC Class B, CE Mark		
100-240V AC, 50/60 Hz		
0.5 W in Eco Standby mode, up-to 320 W		
up-to 1092 BTU/hr		
Kensington® Security Slot		
4571194679366		
Clean Filter, Replace Lamp		
Limited Warranty: to the original end use customer only		
*3 years / 6000 hours		
*1 year ownership / 500 hours use		
*(whichever occurs first)		