


**EK-302X**

5,600 ANSI lumens bright with 80% uniformity and a 8,000:1 contrast ratio.  
Native XGA resolution. Compatible with inputs up-to UXGA and WUXGA.  
Supports analog and digital video input in all color standards up-to 1080p.  
HDMI with MHL (Mobile High-Definition Link) displays HD Video from Smartphones & Tablets.  
Convenient mid-range (1.6:1) manual zoom and focus lens.  
Horiz., Vert. & Corner Keystone Correction.  
Horiz. & Vert. Manual Lens Shift. Wired network control.  
Accepts composite, component, and S-Video in all major standards.  
Displays both 4:3 and 16:9 aspect ratios. Supports most HDTV resolutions.  
Built-in 10 Watt sound system. Closed Caption decoding (NTSC).  
Side-accessed air filter & top accessed lamp for ease of maintenance.  
Pin Cushion / Barrel image correction  
Auto input selection. Built-in Test Patterns.  
Security bar. Kensington® MicroSaver® security slot. PIN lock.  
3 year projector warranty.



**Included Accessories:**

Quick Start Guide, VGA Computer Input Cable (Dsub15 to Dsub15), 6.0 ft (1.8 m) Detachable Power Cord, Remote Control (with 2 AAA Batteries)

**Optional Accessories:**

Replacement Lamp, Component Video Cable (3RCA to Dsub15), S-Video Cable (S-Video to Dsub15), Ceiling Mount, Ceiling Post and Plate

**Specifications: Model EK-302X**

<b>Brightness</b>	5,600 ANSI Lumens	<b>Image Signal Inputs</b>	
<b>Contrast Ratio</b>	8,000:1	<b>Computer 1 (Component / S-Video)</b>	Dsub15 x 1
<b>Illumination Uniformity</b>	80%	<b>Computer 2 (switchable Monitor Out)</b>	Dsub15 x 1
<b>Resolution and Aspect Ratio</b>	XGA (1024x768), 4:3	<b>Digital Video (w/ HDCP &amp; MHL)</b>	HDMI x 2
<b>Color Reproduction</b>	10-bit (16.7 million colors)	<b>USB Type A - Memory Viewer</b>	USB Type A x 1
<b>Projection Lamp</b>	280 Watts UHP	<b>USB Type B - USB Display / Firmware</b>	USB Type B x 1
<b>Estimated Lamp Life (Eco / Normal)</b>	4,000 / 3,000 hours	<b>Composite Video</b>	RCA x 1
<b>Total Pixels</b>	2,359,296 (1024x768) x 3	<b>Audio Signal Inputs</b>	
<b>Imaging System</b>	0.63 in (16 mm) inorganic LCD Panels x 3	<b>Computer Audio</b>	MiniStereo x 1
<b>Scanning Frequency</b>	Auto: H Sync. 15-100 kHz, V Sync. 48-85 Hz	<b>Video Audio</b>	RCA x 2 (L/R)
<b>Pixel Clock</b>	up-to 150 MHz	<b>Outputs</b>	
<b>Lens</b>	Attached - Manual Zoom and Focus	<b>Computer Monitor (Computer 2)</b>	Dsub15 x 1
<b>Lens Specs</b>	f: 1.65-2.65; FL: 0.716-1.156 in (18.2-29.38 mm)	<b>Audio Output</b>	Variable, Stereo; MiniStereo x 1
<b>Lens Ratios</b>	Zoom Max:Min: 1.6:1; Throw:Width 1.4-2.3:1	<b>Amplifier</b>	Mono: 10 Watt
<b>Image Diagonal</b>	40-300 in (101.6-762 cm)	<b>Speaker</b>	1.4 in (3.7 cm) x 1 (Mono)
<b>Image Width</b>	2.6-20 ft (0.79-6.1 m)	<b>Fan Noise (Eco / Normal)</b>	35.5 dB / 40.0 dB
<b>Throw Distance</b>	2.9-35.5 ft (0.88-10.83 m)	<b>Cabinet Size (HxWxD) - excluding legs</b>	5.0 x 12.5 x 15.5 in (12.7 x 31.7 x 39.4 cm)
<b>Projector Elevation Adjustment (legs)</b>	up-to 10°	<b>Weight</b>	9.9 lb (4.5 kg)
<b>Maximum Pitch</b>	Up-to 30° Up or Down	<b>Packaged Cabinet Size (HxWxD)</b>	8.4 x 16.7 x 18.8 in (21.4 x 42.4 x 47.9 cm)
<b>Vert/Horiz. Keystone Correction</b>	Digital:V: +/- 30° (Auto) - H: +/- 15° (Auto), Corner Keystone	<b>Packaged Weight</b>	13.2 lb (6 kg)
<b>Lens Shift</b>	Vertical: 40% (Manual) Horiz.: 10% (Manual)	<b>Operating Temperature</b>	41-95°F (5-35°C)
<b>Image Orientation</b>	Normal, Reversed, Inverted	<b>Electrical Safety Compliance</b>	IEC / UL / cUL
<b>Local Control / Power Management</b>	Full Function / Auto Shutdown	<b>Electromagnetic Compatibility</b>	FCC Class B, CE Mark
<b>Remote Control</b>	Wireless x 1	<b>Power Requirements</b>	100-240V AC, 50/60 Hz
<b>RS-232 Control</b>	Dsub9 x 1	<b>Power Consumption</b>	0.5 W in Eco Standby mode, up-to 345 W
<b>LAN Port</b>	RJ45 x 1	<b>Heat</b>	up-to 1177 BTU/hr
<b>Computer Input in Pixels</b>	up-to 1600x1200 (4:3), 1920x1200 (16:10)	<b>Security Facilities</b>	Kensington® Security Slot
<b>Analog 4x3 Inputs</b>	UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC	<b>UPC</b>	4571194678376
<b>Analog Wide Inputs</b>	WUXGA, WSXGA+, WXGA	<b>User Maintenance</b>	Clean Filter, Replace Lamp
<b>Digital 4x3 Inputs</b>	UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC	<b>Limited Warranty: to the original end use customer only</b>	
<b>Digital Wide Inputs</b>	WUXGA, WSXGA+, WXGA	<b>Projector</b>	*3 years / 6000 hours
<b>Video Formats</b>	NTSC / PAL / SECAM	<b>Lamp</b>	*1 year ownership / 500 hours use (whichever occurs first)
<b>Video Input Analog</b>	480i/p, 575i/p		
<b>Video Input Digital</b>	480p, 575p, 720p, 1080i/p		
<b>Image Signal Resizing</b>	Smart Scaling Technology		

**Lamp contains Mercury. Do not put in trash. Dispose of as Hazardous Waste, according to Local, State or Federal Laws.**  
EIKI® is a registered trademark of Eiki International Inc. Kensington is a registered trademark of ACCO Brands Corporation.